

## MODEL 550H PIPE JOINT LUBRICANT

**SHURJOINT** pipe joint lubricant Model 550H is a tan colored non-toxic paste. The lubricant is recommended for proper gasket installation and to help prevent the gasket from being pinched. The lubricant is applied in a thin coat to the gasket exterior, the gasket lips and/or the housing interiors. **Shurjoint** lubricant is available in one pound (450 grams) and one quart (2 pounds or 900 grams) containers. Certified to ANSI/NSF 61.

### Features:

- Applies equally well to wet or dry surface.
- Contains no petroleum.
- Will not support bacteria.
- Will not deteriorate natural or synthetic rubber, plastic gaskets or cast iron pipe.
- Suitable for all types of pipelines, including potable water pipelines.
- Excellent working range, 0°F to 150°F.
- Will not impart taste, color or odor to water in pipelines flushed in accordance with recommended AWWA procedures.



### Usage Guide:

(Approximate)

Gasket (Inch)	Number of Gaskets	
	One Pound	Two Pounds
2	220	440
3	180	360
4	100	200
6	80	160
8	60	120
10	40	80
12	36	72
14	28	56
16	24	48
18	20	40
20	16	32
24	12	24

### Directions:

1. **Shurjoint** 550H lubricant is ready for use.
2. See Assembly leaflet for detailed instructions pertaining to particular **Shurjoint** pipe joint lubricant being assembled.

## MATERIAL SPECIFICATIONS

### • Compounds:

Name	CAS#
Proprietary blend of soap	61790-44-1
Glycol	57-55-6
Filler	12001-26-2

Job Name:	System No.	Location:
Contractor:	Approved:	Date:
Engineer:	Approved:	Date:

**Shurjoint** product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact **Shurjoint** Technical Service. **Shurjoint** reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligations to make such changes and modifications on **Shurjoint** products previously subsequently sold.

General Notes:

- **Warning:** Piping systems must always be depressurized and drained before attempting disassembly and or removal of any components.
- **Shurjoint** reserves the right to change specifications, designs and or standard equipment without notice and without incurring any obligations..